

### **AMENDMENTS TO THE SPECIFICATION:**

Please replace the paragraph starting on page 5, line 3 with the following amended paragraph.

The door 18 further includes a reinforced bottom edge 32 which is formed by folding over an edge portion of the door upon the front face 28. Similarly, the hook flange 30 includes a reinforced edge 34 formed by folding over a portion of the hook flange 30 upon itself. With reference to Figures 1 and 2, the door 18 includes side flanges 36,38 flanking either side of the front face 28. The side flanges 36,38 extend at respective angles rearwardly from the front face 28. Distal edges of the side flanges 36,38 are formed into U-shaped channel portions each including a rear face portion 40 and a rear reinforcing flange 42. Rubber stoppers 44 are connected to respective rear face portions 40 by suitable fasteners ~~[[46]]~~ such as rivets or the like. The rubber stoppers 44 serve to maintain the door 18 in a position generally parallel to the side of the housing 12. More particularly, without the rubber stoppers 44, the door 18 would likely tilt wherein the reinforced bottom edge 32 would be closer to the side of the housing than a top of the front face 28.

Please replace the paragraph starting on page 6, line 14 with the following amended paragraph.

With additional reference to Figures 2 and 3, both the first and second notches 86,88 are connected to respective first and second slots 74,78 and, as will be described in more detail below, the notches 86,88 allow the door 18 to be removed from the housing 12. Specifically, the second hooked end 50 of the first hook ~~[[22]]~~ 24 is received in the first slot 74 and, likewise, the second hooked end 50 of the second hook 26 is received in the second slot 78. Within their respective slots 74,78, the hooks 24,26 are slidably movable for moving the door 18 along the track member 20. An ultra low friction slide or protector 90, preferably a material like polyethylene acetal or Teflon, is provided along each of the first and second slots 74,78 on a portion of the raised front wall 60 defining a lower end of the slots 74,78 for engaging the hooks 24,26.